



Water cooled  
screw chiller,  
high efficiency,  
standard sound  
EWWD-G-XS

**R-134a**



Screw compressor

- › Stepless single-screw compressor
- › 1-2 truly independent refrigerant circuits
- › Standard electronic expansion valve
- › DX shell and tube evaporator – one pass refrigerant side for easy oil circulation and return

- › Partial and total heat recovery option available


# EWWD-G-XS



Heating only & Cooling only				EWWD-G-XS	190	230	280	320	380	400	460	500	550	650
Cooling capacity	Nom.		kW		185	222	276	306	365	407	443	495	539	602
Heating capacity	Nom.		kW		226	272	337	379	446	496	540	602	657	743
Power input	Cooling	Nom.	kW											
	Heating	Nom.	kW		40.6	49.4	61.0	73.4	81.1	89.0	97.0	107	117	141
Capacity control	Method	Stepless												
	Minimum capacity		%		25.0				12.5					
EER					4.57	4.50	4.53	4.17	4.50	4.58	4.57	4.61	4.59	4.26
ESEER					5.37	5.31	5.33	4.91	5.54	5.62	5.61	5.68	5.67	5.27
COP					5.57	5.50	5.53	5.17	5.50	5.58	5.6	5.61	5.59	5.26
IPLV					6.45	6.36	6.35	5.80	6.47	6.57	6.55	6.65	6.64	6.17
Dimensions	Unit	Height	mm		1,860				1,880					
		Width	mm		920				860					
		Depth	mm		3,435				4,305					
Weight	Unit		kg		1,650	1,665	1,680	2,800	2,945	2,955	2,975	2,990		
	Operation weight		kg		1,800	1,810	1,820	3,020	3,280	3,290	3,315	3,340		
Water heat exchanger - evaporator	Type	Single pass shell and tube												
	Water volume		l		125	120	110	170	285	280				
	Water pressure drop	Cooling	Total	kPa	23	31	30	37	28	21	24	33	39	47
Compressor	Type	Single screw compressor												
	Quantity				1				2					
Sound power level	Cooling	Nom.	dBA		88				90					
Sound pressure level	Cooling	Nom.	dBA		70				72					
Operation range	Evaporator	Cooling	Min.	°CDB										
			Max.	°CDB	-8									
	Condenser	Cooling	Min.	°CDB	15									
			Max.	°CDB	20									
Refrigerant	Type/GWP	R-134a/1,430												
	Circuits	Quantity		1				2						
Refrigerant charge	Per circuit		kg		60.0				65.0	60.0	65.0	60.0		
	Per circuit		TCO <sub>2</sub> Eq		85.8				93.0	85.8	93.0	85.8		
Piping connections	Evaporator water inlet/outlet (OD)	114.3												
	Condenser water inlet/outlet (OD)	139.7												
Unit	Starting current	Max	A		288				380	397		420		438
	Running current	Cooling	Nom.	A	71	81	96	109	142	152	161	174	186	210
		Max	A	114	136	165	186	229	250	272	301	330	373	
Power supply	Phase/Frequency/Voltage		Hz/V	3~/50/400										

Cooling: entering evaporator water temp. 12°C; leaving evaporator water temp. 7°C; entering condenser water temp. 30°C; leaving condenser water temp. 35°C; full load operation. Equipment contains fluorinated greenhouse gases. Actual refrigerant charge depends on the final unit construction, details can be found on the unit labels.

**Daikin Europe N.V.** Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN15-463\_2 03/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.